



## Series PGS Low Cost Pressure Gauge Installation and Operating Instructions

KOBOLD Instruments, Inc. 1801 Parkway View Drive, Pittsburgh, PA 15205  
Telephone: (412) 788-2830 FAX: (412) 788-4890 www.koboldusa.com

### Precautions

**User's Responsibility for Safety:** KOBOLD manufactures a wide range of process sensors and technologies. While each of these technologies are designed to operate in a wide variety of applications, it is the user's responsibility to select a technology that is appropriate for the application, to install it properly, to perform tests of the installed system, and to maintain all components. The failure to do so could result in property damage or serious injury.

**Proper Installation and Handling:** Use a proper sealant with all installations. Never over tighten the sensor within its fittings. Always check for leaks prior to system start-up.

**Temperature and Pressure:** Temperature and pressure maximums vary depending upon the material selected. Operation outside these limitations will cause damage to the unit.

**Material Compatibility:** Make sure that the material of construction is chemically compatible with the application liquids. While the sensor's outer housing is liquid resistant when installed properly, it is not designed to be immersed. It should be mounted in such a way that it does not normally come into contact with fluid.

#### Flammable, Explosive and Hazardous

**Applications:** This unit is not an explosion-proof design. It should not be used in applications where an explosion-proof design is required.

**Make a Fail-Safe System:** Design a fail-safe system that accommodates the possibility of sensor or power failure. In critical applications, KOBOLD recommends the use of redundant backup systems and alarms in addition to the primary system

### Description:

KOBOLD PGS pressure gauges are ideal for rugged applications and harsh environments. The PGS features an ABS housing and a full view polycarbonate window. The PGS movement design offers superior shock, vibration and pulsation resistance.



### Specifications:

<b>Ranges:</b>	0–200 PSIG
<b>Maximum Pressure:</b>	75% of full scale
<b>Sensing Element:</b>	Bourdon tube
<b>Dial size:</b>	2½"
<b>Accuracy:</b>	3-2-3% Grade B
<b>Maximum Temperature:</b>	-40 to 150°F Max
<b>Fitting:</b>	¼" NPT
<b>Materials of Construction</b>	
<b>Wetted Parts</b>	
<b>Tube:</b>	Bronze
<b>Fitting:</b>	Brass
<b>Exterior</b>	
<b>Movement:</b>	Brass/Polyester
<b>Housing:</b>	ABS
<b>Dial:</b>	Black figures on white painted steel
<b>Pointer:</b>	Black painted aluminum
<b>Window:</b>	Polycarbonate (snap-in)